



VACUUM PACKING MACHINE SU-810GP+ 400/50-60/3N

Floorstanding unit. 100m³/h. 530+848 mm.



P/N 1140943



SALES DESCRIPTION

Two sealing bars (530+848 mm.)
100 m³/h Busch vacuum pump.
Vacuum controlled by sensor.

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 25-programme memory. Blocking option.
- ✓ "Pause" button.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber.
- ✓ Damped transparent lid.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.
- ✓ NSF-listed.

INCLUDES

- ✓ Filling plate
- ✓ Inert gas flush (4+3 injectors).
- ✓ Wireless connectivity
- ✓ Printer connection
- ✓ "Plus" sealing system

OPTIONAL

- ☐ Printer
- ☐ Vacuum packing pouches
- ☐ Vac-Norm external vacuum kit, containers and accessories
- ☐ Bag cutting kit
- ☐ Support for liquids
- ☐ Additional filling plates

ACCESSORIES

- ☐ Bag cutting kits
- ☐ Filling plates
- ☐ Liquid insert plates
- ☐ Vac-norm external vacuum kits
- ☐ Vac-norm containers
- ☐ Smooth bags for vacuum packing
- ☐ Thermal labels for CG2 / RB printer
- ☐ RB desktop printer for SU vacuum packing machines
- ☐ Thermal transfer labels for RB printer

SPECIFICATIONS

Pump capacity: 100 m³/h

Bar length: 530 mm + 848 mm

Total loading: 2200 W

Vacuum pressure (maximum): 0.5 mbar

Electrical supply: 400 V- / 50-60 Hz / 3N~ (8.7 A)

Electrical connection: 3P+N+G

Internal dimensions

- ✓ Width: 864 mm
- ✓ Depth: 603 mm
- ✓ Height: 215 mm

External dimensions (W x D x H)

- ✓ Width: 960 mm
- ✓ Depth: 757 mm
- ✓ Height: 998 mm

Net weight: 251 kg

Noise level (1m.): 75 dB(A)

Background noise: 32 dB(A)

Crated dimensions

840 x 1060 x 1200 mm

Gross weight: 292 kg

FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES • SENSOR ULTRA LINE



product sheet
updated 24/05/2024




VACUUM PACKING MACHINE SU-810GP+ 400/50-60/3N

Floorstanding unit. 100m³/h. 530+848 mm.



P/N 1140943

FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES • SENSOR ULTRA LINE



sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project	Date
Item	Qty
Approved	

product sheet
updated 24/05/2024