



DISHWASHER SRC-2700DCA 400/50/3N

100/150 baskets per hour (up to 2.700 plates/hour).

P/N 1302557



SALES DESCRIPTION

Washing + rinsing.
2 speeds.

- ✓ Fully stainless steel jacket.
- ✓ Inlet and outlet splash guards are standard.
- ✓ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

Economy

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- ✓ Programmed automatic stops if there is no loading.
- ✓ Stop and freezing of timer when the limit switch actuates.

Cleaning and maintenance

- ✓ Wide pivoting door allowing access for cleaning or inspection purpose.
- ✓ Detachable arms and dispersers for easier cleaning.
- ✓ Sloped removable stainless steel filters with independent removable basket.
- ✓ Easy boiler emptying by loosening a hose.
- ✓ Failures are easily detected thanks to the warning lights.
- ✓ Easy to repair without moving the machine.

Washing

- ✓ Stainless steel wash arms and deep-drawn dispersers.
- ✓ Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dispenser intake in washing tank. Rinsing

Rinsing

- ✓ Stainless steel rinse arms and powerful, stainless steel, deep-drawn dispersers.
- ✓ Automatic boiler filling with no failure risk for heating elements.

- ✓ Temperature control with high precision probes.
- ✓ Visualisation and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- ✓ Easy to install rinse aid dispenser intake in boiler.

INCLUDES

- ✓ Inlet and outlet splash guards are standard.
- ✓ Extraction hood without motor CA.

OPTIONAL

- ☐ Inlet tables and compositions.
- ☐ Outlet tables and compositions.

ACCESSORIES

- ☐ Manual water softeners
- ☐ Automatic water softeners
- ☐ 500 x 500 mm. baskets
- ☐ Inserts & supplements
- ☐ Loading table for corner situation for rack conveyor dishwashers
- ☐ Central sorting tables
- ☐ Double connection central sorting table
- ☐ Single exit tables
- ☐ Roller conveyor and corner roller conveyor
- ☐ Machined curve
- ☐ Connecting tables for pass-through dishwashers and rack conveyors

SPECIFICATIONS

Production

- ✓ Production baskets/hour: 100 / 150
- ✓ Production plates/hour: 1800 / 2700

Wash

- ✓ Temperature: 55 °C - 65 °C
- ✓ Wash tank capacity: 100 l
- ✓ Pump: 3.2 Hp / 2400 W
- ✓ [s:1av_resist]: 9000 W

Rinse

- ✓ Temperature: 80 °C - 90 °C
- ✓ Water consumption: 330 l/h
- ✓ Rinse heating element: 18000 W
- ✓ Boiler capacity: 20 l

Drag

- ✓ Drag motor power: 0.25 Hp / 180 W

(CA) output diameter: -- mm

Loading

- ✓ Central module total power: 29780 W

External dimensions (WxDxH)

- ✓ Width: 1700 mm
- ✓ Depth: 829 mm
- ✓ Height: 1520 mm

Net weight: 250 Kg

Water Intake: 3/4 "

Drain diameter: 1 1/2 "

Noise level (1m.): 71 dB(A)

Crated dimensions

2550 x 1000 x 1950 mm

Gross weight: 285 Kg



WARE WASHING
RACK CONVEYOR DISHWASHERS

product sheet
updated 15/02/2023






DISHWASHER SRC-2700DCA 400/50/3N

100/150 baskets per hour (up to 2.700 plates/hour).

P/N 1302557

WARE WASHING
RACK CONVEYOR DISHWASHERS



sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project	Date
Item	Qty
Approved	

product sheet
updated 15/02/2023