



REVERSE OSMOSIS DEVICE OS-140P 230/50/1



P/N 5320140



SPECIFICATIONS

Membranes: 4 x TWG1A1
Internal pre-filter: Profine BLUE small
Total loading: 180 W

Water flow data

- ✓ Maximum water inlet flow: 300 l/h
- ✓ Maximum temperature: 35 °C
- ✓ Feed water pressure (bar) (max): 5 bar
- ✓ Feed water pressure (bar) (min): 1.5 bar

Permeate specifications

- ✓ ___ Maximum capacity (10°C): 140 l/h
- ✓ Recovery percentage: 25-60%
- ✓ Electrical supply: 230 V / 50 Hz / 1 ~ (1.8 A)
- Noise level (1m.): <70 dB(A)
- External dimensions (WxDxH): 168 mm x 515 mm x 476 mm
- Net weight: 20 Kg

Crated dimensions

190 x 720 x 520 mm
Gross weight: 29 Kg.

SALES DESCRIPTION

Reverse osmosis equipment for industrial, professional and catering applications.

Simplicity and speed.

Suitable for dishwashers with or without a break tank.

Reverse osmosis provides excellent finish, specially in glassware, and accelerates the drying process of the wares.

- ✓ The purifier ensures a high and immediate flow which, combined with high pressure, allows fast and continuous washing cycles.

WARE WASHING
PASS-THROUGH DISHWASHERS



sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1. phone +34 943 15 72 36
20720 Azkoitia, Spain sales@sammic.com



Project	Date
Item	Qty
Approved	

product sheet
updated 12/11/2021